



N-Channel 30-V (D-S) MOSFET


PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
30	0.012 @ $V_{GS} = 10$ V	12.5
	0.018 @ $V_{GS} = 4.5$ V	10.2

FEATURES


- TrenchFET® Power MOSFET
- Lead (Pb)-Free Version is RoHS Compliant



Pb-free
Available



Ordering Information: Si4894DY-T1
Si4894DY-T1—E3 (Lead (Pb)-Free)



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)					
Parameter		Symbol	10 secs	Steady State	Unit
Drain-Source Voltage		V_{DS}	30		V
Gate-Source Voltage		V_{GS}	± 20		
Continuous Drain Current ($T_J = 150^\circ\text{C}$) ^a	$T_A = 25^\circ\text{C}$	I_D	12.5	8.5	A
	$T_A = 70^\circ\text{C}$		10	6.8	
Pulsed Drain Current		I_{DM}	20		
Continuous Source Current (Diode Conduction) ^a		I_S	2.7	1.3	A
Maximum Power Dissipation ^a	$T_A = 25^\circ\text{C}$	P_D	3.0	1.4	W
	$T_A = 70^\circ\text{C}$		1.9	0.9	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150		$^\circ\text{C}$

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^a	$t \leq 10$ sec	R_{thJA}	35	42	$^\circ\text{C/W}$
	Steady State		73	90	
Maximum Junction-to-Foot (Drain)		R_{thJF}	16	20	

Notes

a. Surface Mounted on 1" x 1" FR4 Board.



SPECIFICATIONS (T_J = 25 °C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit	
Static							
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	0.8		1.8	V	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 30 V, V _{GS} = 0 V			1	μA	
		V _{DS} = 30 V, V _{GS} = 0 V, T _J = 55 °C			5		
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 10 V	30			A	
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 10 V, I _D = 12.5 A		0.010	0.012	Ω	
		V _{GS} = 4.5 V, I _D = 10.2 A		0.015	0.018		
Forward Transconductance ^a	g _{fs}	V _{DS} = 15 V, I _D = 12.5 A		30		S	
Diode Forward Voltage ^a	V _{SD}	I _S = 2.7 A, V _{GS} = 0 V		0.7	1.1	V	
Dynamic^b							
Total Gate Charge	Q _g	V _{DS} = 15 V, V _{GS} = 5 V, I _D = 12.5 A		11.5	17	nC	
			V _{DS} = 15 V, V _{GS} = 10 V, I _D = 12.5 A		20		30
							3.0
Gate-Source Charge	Q _{gs}			4.5			
Gate-Drain Charge	Q _{gd}						
Gate Resistance	R _g		0.5		2.4	Ω	
Turn-On Delay Time	t _{d(on)}	V _{DD} = 15 V, R _L = 15 Ω I _D ≅ 1 A, V _{GEN} = 10 V, R _g = 6 Ω		10	20	ns	
Rise Time	t _r			5	10		
Turn-Off Delay Time	t _{d(off)}			30	60		
Fall Time	t _f			10	20		
Source-Drain Reverse Recovery Time	t _{rr}	I _F = 2.7 A, di/dt = 100 A/μs		30	60		

Notes







- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)







TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)





TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?71162>.