


Device Modeling Report

COMPONENTS: OPERATIONAL AMPLIFIER
PART NUMBER: NJM064
MANUFACTURER: NEW JAPAN RADIO CO., LTD



Bee Technologies Inc.

Spice Model




```

*$
* PART NUMBER: NJM064
* MANUFACTURER: NEW JAPAN RADIO
* All Rights Reserved Copyright (c) Bee Technologies Inc. 2004
.Subckt NJM064 OUT1 -IN1 +IN1 V+ +IN2 -IN2 OUT2 OUT3 -IN3 +IN3 V-
+ +IN4 -IN4 OUT4
X_U1  +IN1 -IN1 V+ V- OUT1 NJM064_ME
X_U2  +IN2 -IN2 V+ V- OUT2 NJM064_ME
X_U3  +IN3 -IN3 V+ V- OUT3 NJM064_ME
X_U4  +IN4 -IN4 V+ V- OUT4 NJM064_ME
.ends NJM064
.subckt NJM064_ME 1 2 3 4 5
c1 11 12 2.5981E-12
c2 6 7 9.0000E-12
css 10 99 1.0000E-30
dc 5 53 dy
de 54 5 dy
dlp 90 91 dx
dln 92 90 dx
dp 4 3 dx
egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5
fb 7 99 poly(5) vb vc ve vlp vln 0 6.3660E6 -1E3 1E3 6E6 -6E6
ga 6 0 11 12 51.832E-6
gcm 0 6 10 99 1.7339E-9
iss 3 10 dc 38.000E-6
hlim 90 0 vlim 1K
j1 11 2 10 jx1
j2 12 1 10 jx2
r2 6 9 100.00E3
rd1 4 11 15.915E3
rd2 4 12 15.915E3
ro1 8 5 50
ro2 7 99 25
rp 3 4 1.8000E3
rss 10 99 5.2632E6
vb 9 0 dc 0
vc 3 53 dc 1.4788
ve 54 4 dc 1.6788
vlim 7 8 dc 0
vlp 91 0 dc 7.5000
vln 0 92 dc 7.5000
.model dx D(Is=800.00E-18)
.model dy D(Is=800.00E-18 Rs=1m Cjo=10p)
.model jx1 PJF(Is=242.50E-12 Beta=79.120E-6 Vto=-.9925)
.model jx2 PJF(Is=142.50E-12 Beta=79.120E-6 Vto=-1.007500)
.ends
*$


```

Output Voltage Swing, +Vout and -Vout

Simulation result




Evaluation circuit




Output Voltage Swing	Data sheet	Simulation	%Error
+Vout(V)	+14.200	+14.290	0.633
-Vout(V)	-14.000	-14.090	0.642

Input Offset Voltage

Simulation result




Evaluation circuit




Vos	Measurement		Simulation		Error	
	15.000	mV	14.985	mV	0.100	%

Slew Rate, +SR, -SR

Simulation result




Evaluation circuit




Slew Rate(v/us)	Data sheet	Simulation	%Error
	3.500V/us	3.475V/us	0.714

Input current Ib, Ibos

Simulation result



Evaluation circuit




	Data sheet	Simulation	%Error
Ib(pA)	400.000	400.150	0.037
Ibos(pA)	200.000	200.060	0.030

Open Loop Voltage Gain vs. Frequency , Av-dc, f-0dB

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
f-0dB(MHz)	1.000	1.000	0.000
Av-dc	80.000	80.100	0.125

Common-Mode Rejection Voltage gain

Simulation result



Evaluation circuit



Common Mode Reject Ratio= $10115/0.275=36781$

CMRR	Data sheet	Simulation	%Error
	90.000	91.312	1.458