


Device Modeling Report

COMPONENTS: OPERATIONAL AMPLIFIER
PART NUMBER: NJM2100
MANUFACTURER: NEW JAPAN RADIO CO., LTD



Bee Technologies Inc.

Spice Model



NJM2100


```

*$
* PART NUMBER: NJM2100
* MANUFACTURER: NEW JAPAN RADIO
* All Rights Reserved Copyright (c) Bee Technologies Inc. 2005
.Subckt NJM2100 OUT1 -IN1 +IN1 V- +IN2 -IN2 OUT2 V+
X_U1  +IN1 -IN1 V+ V- OUT1 NJM2100_ME
X_U2  +IN2 -IN2 V+ V- OUT2 NJM2100_ME
.ends NJM2100
.subckt NJM2100_ME 1 2 3 4 5
c1 11 12 1.0000E-12
c2 6 7 26.000E-12
dc 5 53 dy
de 54 5 dy
dlp 90 91 dx
dln 92 90 dx
dp 4 3 dx
egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5
fb 7 99 poly(5) vb vc ve vlp vln 0 175.00E3 -1E3 1E3 180E3 -180E3
ga 6 0 11 12 2.1619E-3
gcm 0 6 10 99 451.32E-9
iee 3 10 dc 120.20E-6
hlim 90 0 vlim 1K
q1 11 2 13 qx1
q2 12 1 14 qx2
r2 6 9 100.00E3
rc1 4 11 442.10
rc2 4 12 442.10
re1 13 10 11.009
re2 14 10 11.009
ree 10 99 1.6638E6
ro1 8 5 50
ro2 7 99 25
rp 3 4 50.060
vb 9 0 dc 0
vc 3 53 dc 1.0979
ve 54 4 dc 1.0979
vlim 7 8 dc 0
vlp 91 0 dc 20
vln 0 92 dc 20
.model dx D(Is=800.00E-18)
.model dy D(Is=800.00E-18 Rs=1m Cjo=10p)
.model qx1 PNP(Is=800.00E-18 Bf=560.75)
.model qx2 PNP(Is=827.3700E-18 Bf=618.56)
.ends
*$


```

Output Voltage Swing

Simulation result




Evaluation circuit




Output Voltage Swing	Data sheet	Simulation	%Error
+Vout(V)	2.200	2.199	-0.045
-Vout(V)	-2.200	-2.199	-0.045

Input Offset Voltage

Simulation result




Evaluation circuit




Vos	Measurement		Simulation		Error	
	1.000	mV	1.000	mV	0.000	%

Slew Rate

Simulation result




Evaluation circuit




Slew Rate(v/us)	Data sheet	Simulation	%Error
	4V/us	4.140V/us	3.500

Input current

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
Ib(nA)	100.000	100.087	0.087

Open Loop Voltage Gain vs. Frequency

Simulation result




Evaluation circuit




	Data sheet	Simulation	%Error
f-0dB(MHz)	12.000	11.576	-3.533
Av-dc(dB)	80.000	79.490	-0.638

Common-Mode Rejection Voltage gain

Simulation result



Evaluation circuit



Common Mode Reject Ratio= $9429.746/1.9802=4762.017$

CMRR	Data sheet	Simulation	%Error
	74.000	73.555	-0.601