

FS-1010

PRINTER

Print Speed	Up to 14ppm A4
Processor	PowerPC405 200MHz
Scanning System	Laser
Printing Method	Electrophotographic
Resolution	600x600dpi, Fast1200 (1800x600dpi)
Resolution Enhancement	Up to 2400 x 600 dpi with Kyocera Image Refinement 2 (KIR2)
Duty Cycle	maximum 8,000 pages per month average 2,700 pages per month

MEMORY

RAM	16MB RAM
Maximum RAM	144MB (DIMM 1 slot)
System ROM	4MB DIMM

PRINTER CONTROL LANGUAGES

Standard Emulations	PCL6 (PJL) Diablo 630 IBM proprinter X24E Line Printer Epson LQ850 PostScript Level 2 emulation (KPDLL2)
Controller Language	Prescribe IIe

RESIDENT FONTS

Internal Scalable Typefaces	80 (Outline PCL6 fonts & KPDLL2 fonts supporting an International character set) + 1 fonts
Internal Bitmapped Typefaces	
Downloadable Fonts	Kyocera, HP & TrueType format, Type 1 font format
Internal Barcodes	45 Types (one dimension) + 1 Type (two dimension - PDF417)

STANDARD INTERFACES

Interface	IEEE 1284-1 compliant high speed bi-directional parallel + USB 1.1 interface
-----------	---------------------------------------------------------------------------------

PAPER HANDLING

Standard paper feed capacity	250-sheet universal cassette. 50-sheet multi-purpose / manual feed tray.
Paper Size Supported	A4, A5, B5, Letter, Legal, Custom (148 x 210 to 216 x 297mm) via cassette; 70 x 148 to 216 x 297mm via multi-purpose feed
Paper Specification*	60-105gsm paper (plain, thick, recycled) via cassette; plus OHP film, post card, envelopes and labels, 60-163gsm via multi-purpose feed.
Paper Output	150 sheets face down + 30 sheets face up

BASIC SPECIFICATIONS

Dimensions (HxWxD)	222 x 377.6 x 374.5mm
Weight	9.5Kg
Time to first print	12 seconds
Ozone emission	0.02 mg/m3
Noise Level	50dB printing, 28dB standby
Power Consumption	265W printing, 13W idling, Approx. 5W power save mode (Energy Star Compliant)
Power	220/240V, 50/60Hz

CONSUMABLES

Toner Kit	TK-17 (6,000 pages @ 5% A4 coverage)
Starter Toner	Approx 3,000 pages (@ 5% A4 coverage)
Toner Kit Components	1x toner cartridge 1x user manual 1x recyclable plastic bag (for the disposal of the old toner cartridge) 1x wiper cloth (lint-free)
Toner Composition	Microfine Ceramic Toner

ENHANCEMENTS

Memory upgrades/DIMM-xx	16, 32, 64 & 128MB DIMMs
Paper feeder/PF-17	250-sheet universal cassette. (Max 1 per printer)
Serial interface/IB-10E	RS232C/RS422A Serial Interface
Network Card/IB-21/21e	10/100BaseT Network Interface Card
/IB-20	10Base2/10/100BaseT Network Interface Card
Compact Flash/CF-xx	16, 32, 48MB Compact Flash cards



CONNECTIVITY COMPATIBILITY

SNMP-compliant multi protocol network interface cards	Multi-protocol network interface cards 10Base2 / 10BaseT / 100BaseT Ethernet / TCP/IP IPX/SPX Ethertalk
High speed serial interface	

WARRANTY

3 year Return to Base warranty as standard.
Warranty void if maintenance is not carried out.
Refer to Warranty Card for terms and conditions.

Additional on-site KyoCare warranty upgrades available.

www.kyoceramita.com.au

SYDNEY HEAD OFFICE
6-10 Talavera Road,
North Ryde NSW 2113
Phone 02 9888 9999
Fax 02 9888 9588

MELBOURNE OFFICE
Unit 2, 993 North Road
Murrumbeena VIC 3163
Phone 03 9579 1555
Fax 03 9579 1544

BRISBANE OFFICE
Cnr Forbes Street & Riverside Drive
West End QLD 4101
Phone 07 3876 2032
Fax 07 3876 6277

PERTH OFFICE
Unit 5, Scarborough Beach Rd
Osborne Park WA 6017
Phone 08 9201 9155
Fax 08 9201 9511

Australia Wide Numbers: Sales - 1300 364 429

*Conditions Apply - please refer to User Manual

Service & Support - 1300 368 885

